



garland
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


Part No: SF16RW

Description	Solid 23AWG PACW, 2 Cores Twisted, V-90 PVC Insulation.
Suitable Applications	For the interconnection of detonators and related shot firing equipment.

Cable Construction Drawing



Cable Construction Relative Parts



Cable Description

Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
	23	1/0.61	0.292	0.61	PACW
Insulation	Cores : 2 Material : V-90 PVC Colour : Red/White Nominal Thickness (mm) : 0.4 Nominal OD (mm) : 1.5				
Twisting	Nominal OD (mm) : 2.9				

Jumper Wire

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland

SF16RW-150331.docx

made by



madison



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Electrical Properties

Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	62.2Ω/km
Min. Insulation Resistance @ 20°C	50MΩ.km
Voltage Test: Conductor to core	1.0 kV ac/1min

Mechanical Properties

Operating Temperature Range	-15 to 90°C
Approximate Mass	0.95kg/100m

Supply Information

Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
100m	Plastic Reel	7 x 4.5 x 2.5"	20R	
200m	Plastic Reel	7 x 4.5 x 5"		
250m	Plastic Reel	7 x 4.5 x 5.5"	8R	
500m	Plastic Reel	276 x 120mm	4R	

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

With Garland, you are always well connected.

Sales Enquiries **1800 66 99 99**
www.madisontech.com.au/garland

SF16RW-150331.docx

