



garland
cables

pro series


Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MCP7032FRHFRD

Description	2 cores x 0.75mm ² stranded PACW (7/0.37mm), LSZH (X-HF-110) insulated, cabled, overall LSZH (X-HFS-110-TP) sheathed, WS51-W rated 2 hour fire resistant cable to AS 3013.
Applicable Standards	AS 1670, AS/NZS 3013, AS/NZS 3808, AS/CA S-008, AS 1049
Suitable Applications	Used for fire alarm systems where prolonged exposure to fire and sprinklers is required.

Cable Construction Drawing



Cable Description				
Conductor	Conductor Area (mm ²)	# of Strands	Material	Conductor Class
	0.75	7	PACW	2
Insulation	# of Pairs : 1 Material : LSZH X-HF-110 with flame barrier Colour : Wire 1: Red Wire 2: White Nominal OD (mm) : 3.6			
Sheath	Material : UV stabilized LSZH HFS-110-TP Colour : Red Nominal OD (mm) : 9.8			

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland

MC7032FRHFRD180215

made by



madison



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Electrical Properties

Max. Conductor DC Resistance @ 20°C	24.5 Ω /km
Voltage Rating	450/750V

Mechanical Properties

Operating Temperature Range	-15 to 110°C
AS 3013 rating	WS51-W
Max. Recommended Pulling Tension	190 N
Min. Bend Radius (install)	130 mm
Approximate Mass	12.5 kg/100m

Supply Information

Pack Size	Pack Type	Dimensions	Packs Per Pallet
100m	Wooden Spool	F36 x H18 cm	45
200m	Wooden Spool	F37 x 31 cm	18 or 27
500m	Wooden Drum	F55 x 31 cm	8 or 12

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

With Garland, you are always well connected.

Sales Enquiries **1800 66 99 99**
www.madisontech.com.au/garland

MC7032FRHFRD180215

