



Industrial / Power / Data / Security / Fibre

**Garland's Pro Series** range is the experts' choice for high quality cables.

## Part No: MC7032FRSHFRD

Description	2 cores x 0.75mm <sup>2</sup> stranded PACW, LSZH (X-HF-110) insulated, cabled, overall screened with an Aluminium laminate tape and 7/0.25mm tinned annealed copper draing wire, overall LSZH (X-HFS-110-TP) sheathed, WS51-W rated 2 hour fire resistant screened cable to AS 3013.
Applicable Standards	AS 1670, AS/NZS 3013, AS/NZS 3808, AS/CA S-008, AS 1049
Suitable Applications	Used for fire alarm systems where prolonged exposure to fire and sprinklers is required.

## **Cable Construction Drawing**







Cable Description				
Conductor	Nominal Conductor Area (mm²)	# of Strands	Material	Conductor Class
	0.75	7	PACW	2
Insulation	# Cores : Material : Colour : Nominal OD (mm) :	2 LSZH X-HF-110 with flame barrier Wire 1: Red Wire 2: White 3.6		
Screen		Aluminium Polyester Laminate 100%		

With Garland, you are always well connected.







## Industrial / Power / Data / Security / Fibre

## Garland's Pro Series range is the

experts' choice for high quality cables.

Drain Wire	AWG	Standing		Material
	22	7/0.25		TACW
Sheath	Material:		HFS-110-TP (LSZH) UV stabilized	
	Colour:		Red (RAL 3000)	
	Diameter:		10.10 mm ± 0.20 mm	

Electrical Properties	
Max. Conductor DC Resistance @ 20°C	18.1 Ω/km
Voltage Rating	450/750V
Mechanical Properties	
Operating Temperature Range	-15 to 110℃
AS 3013 rating	WS51-W
Max. Recommended Pulling Tension	190N
Min. Bend Radius (install)	135mm
Approximate Mass	13.7kg/100m

Supply Information			
Pack Size	Pack Type	Dimensions	Packs Per Pallet
500m	Wooden Drum	F55 x 31 cm	8 or 12

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

