



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


Part No: JW45

Description	Solid 24AWG PACW, 4 Cores Twisted, PVC Insulation.
Applicable Standards AS/CA S-S008	
Suitable Applications	For the wiring of electronic and allied equipment and for the
	interconnection of internal telephone frames.
	Not intended for direct connection to mains power.

Cable Construction Drawing

Cable Construction Relative Parts











Cable Description						
Conductor	AWG	Area(mm ²)	Stranding	Diameter(mm)	Material	
	24	0.2	1/0.5	0.5	PACW	
Insulation	Cores:		4			
	Material	:	PVC	PVC		
	Colour:		Red, White	Red, White, Light Blue, Black		
	Nominal Thickness (mm):		: 0.25	0.25		
	Nominal OD (mm):		1.0	1.0		
Twisting	Nominal OD (mm): 2.4					

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Electrical Properties				
Voltage Rating	ELV			
Max. Conductor DC Resistance @ 20°C		93.8Ω/km		
Min. Insulation Resistance @ 20°C		1000MΩ.km		
Voltage Test: Conductor to core		1.5kV ac/1min		
Mechanical Properties				
Operating Temperature Range		-15 to 90°C		
Approximate Mass		1.08kg/100m		
Supply Information				
Pack Size Pack Type	Dimensions	Otv Per Carton	Cartons Per Pallet	

Supply Information						
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet		
100m	Plastic Reel	7 x 4.5 x 2.5"				
250m	Plastic Reel	10 x 4.5 x 2"				
500m	Plastic Reel	10 x 4.5 x 4"				

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

