Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

A0270165 Connectivity Accessories - GigaBIX and BIX Connecting Tool

General Description: GigaBIX and BIX Connecting Tool, Cameleon Gray Usage (Overall) suitable Applications: To terminate cables, pigtals or cross-connect wires on any GigaBIX or BIX product. Related Parts: GigaBIX and BIX Connector, Tool Pouch, Pigtals, Cross-Connect Wire. Physical Characteristics (Connectivity) Dimensions Dimensions: Vietight 0,1000 0,100 Color: Cameleon Gray Weight: 0,250 bs. Packaging Packaging Individual packaged in caton. Mechanical Characteristics (Connectivity) Storage Temperature Range: 40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability Suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Notes: (Overall)				6		à		For more Information please call 1-800-Belden1	
Usage (Overall) To terminate cables, pigtails or cross-connect wires on any GigaBIX or BIX product. Related Parts: GigaBIX and BIX Connector, Tool Pouch, Pigtails, Cross-Connect Wire. Physical Characteristics (Connectivity) Dimensions Dimensions: width (in) Depth (in.) Length (in.) 1:500 1:000 Color Color Color Color Veight: 0:250 lbs. Packaging Individual packaged in carton. Packaging Individual packaged in carton. Mechanical Characteristics (Connectivity) Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Yes - Indoor	General Description:								
Suitable Applications: To terminate cables, pigtalis or cross-connect wires on any GigaBIX or BIX product. Related Parts: GigaBIX and BIX Connector, Tool Pouch, Pigtalis, Cross-Connect Wire. Physical Characteristics (Connectivity) Immediate addition of the second	GigaBIX and BIX Connecting Tool, Cameleon Gray								
Related Paris: GigaBIX and BIX Connector, Tool Pouch, Pigtalis, Cross-Connect Wire. Physical Characteristics (Connectivity) Dimensions Dimensions: Width (in,) Depth (in,) Length (in) 1.500 1.000 Color Cameleon Gray Weight 0.250 lbs. Packaging Individual packaged in carton. Mechanical Characteristics (Connectivity) Storage Temperature Range: Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -40°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability Suitability Indoor Yes - Indoor Yes - Indoor	Usage (Overall)								
Physical Characteristics (Connectivity) Dimensions Width (in.) Depth (in.) Length (in.) 1:500 1:000 Color Color Color Color Color Color Packaging Packaging Packaging Individual packaged in carton. Mechanical Characteristics (Connectivity) Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -40°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability Suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Yes - Indoor Notes (Overall) Yes - Indoor	Suitable Applications:			To te	erminate cables,	pigtails or cross-	connect wires on any GigaBIX or BIX produ	ict.	
Dimensions Width (in) Depth (in.) Length (in.) 1:00 6:100 Color: Cameleon Gray Weight: 0.250 lbs. Packaging: 0.250 lbs. Packaging: 0.250 lbs. Packaging: Individual packaged in carton. Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Ves - Indoor Stutability - Indoor: Yes - Indoor Yes - Indoor Yes - Indoor	Related Parts:	Related Parts:			GigaBIX and BIX Connector, Tool Pouch, Pigtails, Cross-Connect Wire.				
Dimensions Width (in) Depth (in.) Length (in.) 1:00 6:100 Color: Cameleon Gray Weight: 0.250 lbs. Packaging: 0.250 lbs. Packaging: 0.250 lbs. Packaging: Individual packaged in carton. Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Ves - Indoor Stutability - Indoor: Yes - Indoor Yes - Indoor Yes - Indoor	Physical Characteristics (Connectivity)								
Weight 0.250 lbs. Packaging Individual packaged in carton. Packaging: Individual packaged in carton. Mechanical Characteristics (Connectivity) Storage Temperature Range: Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability Yes - Indoor Transmission Characteristics (Connectivity) Notes (Overall)	Dimensions Dimensions: Width (in.) Depth (in.) 1.500 1.000	Length (in.)							
Weight: 0.250 lbs. Packaging Individual packaged in carton. Packaging: Individual packaged in carton. Mectanical Characteristics (Connectivity) -40°C To +70°C Installation Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Yes - Indoor Suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Yes - Indoor	Color:			Carr	neleon Gray				
Packaging Individual packaged in carton. Mechanical Characteristics (Connectivity) 40°C To +70°C Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability - Indoor: Suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Yes - Indoor	Weight								
Packaging: Individual packaged in carton. Mechanical Characteristics (Connectivity) 40°C To +70°C Storage Temperature Range: -40°C To +60°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability Suitability Indoor Yes - Indoor Yes - Indoor Transmission Characteristics (Connectivity) Notes (Overall)	Weight:				0.250 lbs.				
Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability Suitability Suitability Suitability Suitability Notes (Overall)				Indiv	vidual packaged	in carton.			
Installation Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Suitability Suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Notes (Overall)	Mechanical Characteristics (Connectivity)								
Applicable Specifications and Agency Compliance (Overall) Suitability Suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Notes (Overall)	Storage Temperature Range:				-40°C To +70°C				
Suitability Yes - Indoor Suitability - Indoor: Yes - Indoor Transmission Characteristics (Connectivity) Notes (Overall)	Installation Temperature Range:				C To +60°C				
Notes (Overall)	Suitability								
Notes (Overall)	Transmission Characteristics (Connectivity)								
			, , ,						
	. ,	e at http://www.be	elden.com						
Product Family									
Put Ups and Colors:									
Item # Putup Ship Weight Color Notes Item Desc		Putun	Shin Weight		Color	Notes	Item Desc		
A0270165 1 EA 0.255 LB BIX CONNECTING TOOL		•				1000			

Revision Number: 0 Revision Date: 03-30-2010

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

^{© 2015} Belden, Inc All Rights Reserved.